



KP12-5

► 12V5Ah


KP12-5 is a general purpose battery up to 5 years in standby service. As with all batteries, all are rechargeable, highly efficient, leak proof and maintenance free.



► Specification

Cells Per Unit	6
Voltage Per Unit	12
Capacity	5.0Ah @ 20hr-rate to 1.75V per cell @25°C (77°F)
Weight	Approx. 1.48 kg(3.26 lbs)
Maximum Discharge Current	75A(5sec)
Internal Resistance	Approx. 25 mΩ
Operating Temperature Range	Discharge: -15°C~50°C (5°F~122°F) Charge: -15°C~40°C (5°F~104°F) Storage: -15°C~40°C (5°F~104°F)
Nominal Operating Temperature Range	25°C±3°C (77°F±5°F)
Float Charging Voltage	13.5 to 13.8 VDC/unit Average at 25°C (77°F)
Recommended Maximum Charging Current Limit	1.5A
Equalization and Cycle Service	14.4 to 14.8 VDC/unitAverage at 25°C (77°F)
Self Discharge	Batteries can be stored for more than 6 months at 25°C (77°F).Please charge batteries before using. For higher temperatures the timeinterval will be shorter.
Terminal	F2-Faston Tab 250
Container Material	ABS(UL 94-HB) & Flammability resistance of (UL 94-V0) can be available upon request.


► Dimensions :	Overall Height (H)	Container height (h)	Length (L)	Width (W)
Unit: mm	105±1.5	100±1.5	90±1.5	70±1




Constant Current Discharge Characteristics								Unit:A (25°C, 77°F)
F.V/Time	5min	15min	30min	1h	3h	5h	10h	20h
1.60V	16.1	9.2	5.28	2.92	1.30	0.858	0.474	0.254
1.67V	15.8	9.0	5.24	2.89	1.29	0.851	0.472	0.253
1.7V	15.6	8.8	5.19	2.86	1.28	0.845	0.469	0.252
1.75V	14.8	8.4	5.09	2.79	1.26	0.831	0.465	0.250
1.8V	13.3	7.8	4.89	2.66	1.21	0.806	0.455	0.245
1.85V	10.3	6.5	4.51	2.43	1.10	0.750	0.430	0.235

Constant Power Discharge Characteristics								Unit:W (25°C, 77°F)
F.V/Time	5min	15min	30min	1h	3h	5h	10h	20h
1.60V	27.6	17.6	10.21	5.55	2.55	1.674	0.933	0.503
1.67V	26.4	16.7	10.14	5.50	2.53	1.667	0.928	0.502
1.7V	25.5	16.2	10.07	5.46	2.51	1.658	0.922	0.500
1.75V	23.3	14.9	9.90	5.38	2.47	1.632	0.912	0.496
1.8V	20.1	13.3	9.52	5.20	2.38	1.578	0.893	0.487
1.85V	15.6	11.2	8.78	4.83	2.20	1.493	0.851	0.469


Trickle(or Float)Design Life




Capacity Retention Characteristic




Battery Voltage and Charge Time for Standby Use




Cycle Service Life



Battery Voltage and Charge Time for Cycle Use



Terminal Voltage (V) and Discharge Time



Charging Procedures

Application	Charge Voltage(V/Cell)			Max.Charge Current
	Temperature	Set Point	Allowable Range	
Cycle Use	25°C(77°F)	2.45	2.40~2.50	0.3C
Standby	25°C(77°F)	2.275	2.25~2.30	

Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/Cell	1.75	1.70	1.65	1.60
Discharge Current(A)	0.2C>(A)	0.2C<(A)<0.5C	0.5C<(A)<1.0C	(A)>1.0C

Effect of temperature on capacity (20HR) Self-discharge Characteristics

Temperature	Dependency of Capacity (20HR)
40°C	102%
25°C	100%
0°C	85%
-15°C	65%

Charge Voltage(V/Cell)	Charge Voltage(V/Cell)
3 Months	91%
6 Months	82%
12 Months	64%